## Finishing Sealer 5800 SERIES 2K HIGH SOLID URETHANE SEALER



**Archemya's 5800 Series 2K High Solid Urethane Sealer** is two component urethane sealer that requires no sanding and has excellent application properties. This sealer will enhance the appearance of clear and base coats by filling in the imperfections of the sanding primers applied over the substrate. This product will bring out the gloss as well as a smooth and even appearance on the finished product after application of sealer.

- BEST USED OVER 2K HIGH BUILD PRIMERS
- EXCELLENT FILLING PROPERTIES TO CREATE A UNIFORM SURFACE
- ◆ EASY TO USE 4:1 RATIO
- ◆ FAST NIB SANDING: ~30 MINUTES @ 50% RELATIVE HUMIDITY
- ◆ AVAILABLE IN BOTH 2.1 AND 4.6 VOC TO MEET ALL VOC STANDARDS
- ◆ AVAILABLE IN WHITE, BLACK, LIGHT GRAY AND DARK GRAY
- EASY TO USE AND COST EFFICIENT

VOC Content	2.1 lb./gal	4.4 lb./gal
% Solids (Mix)	37-40%	37-40%
Pot Life	2 hrs.**	2-3 hrs.**
Mixed Viscosity (#2 Zahn)	21-23 sec.	22-24 sec.
Cure Time (70°F)	30-60 min**	30-60 min**
Recommended Coats	1-2 Coats	1-2 Coats

You can add up to 5% solvent by volume for a reduced viscosity application

**Directions for Use:** For best results, carefully follow the instructions on the can. For more information about this product please refer to our Technical Data Sheet at www.ccgproducts.com.



<sup>\*\*</sup>Dependent on Temperature