## Sanding Primers 7020 SERIES 1K KWIK SANDING PRIMER SURFACER



**Archemya'a 1K Kwik Lacquer Sanding Primer Surfacer** is an advanced elastomeric coating that facilitates adhesion when priming to the surface of plastic, metal, aluminum, urethane, and other substrates. Use **Archemya's 4550 Series Adhesion Promoter** when used over **TPO substrates**. Use low air pressures to get adequate atomization and allow a greater transfer efficiency.

Available in: 7010 (3.5 VOC), 7020 (2.1 VOC) & 7030 (Aerosol)

- PROVIDES SUPERIOR ADHESION (PREVENTS PEELING)
- DRIES QUICKLY AND EASY TO SAND
- GREAT COLOR HOLD OUT
- WORKS ON FLEXIBLE AND RIGID PLASTICS AND SANDED METALS
- **+ EXCELLENT BUILD AND FILLING**
- **+ FAST CURE TIME**
- AVAILABLE IN LIGHT GRAY AND MEDIUM GRAY
- COMES IN QUART, GALLON AND AEROSOL SIZES
- ◆ AVAILABLE IN 3.5 AND 2.1 VOC TO MEET ANY REGULATION

VOC Content	2.1 lb./gal	3.5 lb./gal
% Solids(Mix)	48%	50%
Cure Time	1-1½ Hrs.**	1-1½ Hrs.**
Flash Time	5 min.**	5 min.**

You can add up to 5% solvent by volume for lower viscosity application.

**Directions for Use:** For best results, carefully follow the instructions on the can. For more information about this product please refer to our Technical Data Sheet at www.ccgproducts.com.





<sup>\*\*</sup>Dependent on Temperature.